

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 December 2001 (20.12.2001)


(10) International Publication Number
WO 01/97478 A2

PCT

- (51) **International Patent Classification⁷:** **H04L 27/26** R.; 9309 138 Court, NE, Redmond, WA 98052 (US).
MCMEEKIN, Steven, E.; 1115 Lazy Z Road, Nederland, CO 80301 (US).
(21) **International Application Number:** PCT/US01/15891
(22) **International Filing Date:** 16 May 2001 (16.05.2001) (74) **Agents:** CANAVAN, Robert, T. et al.; AT & T Corp., P.O. Box 4110, Middletown, NJ 07748-4110 (US).
(25) **Filing Language:** English (81) **Designated States (national):** BR, CA, MX.
(26) **Publication Language:** English (84) **Designated States (regional):** European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
(30) **Priority Data:**
09/592,961 13 June 2000 (13.06.2000) US
(71) **Applicant:** AT & T WIRELESS SERVICES, INC. [US/US]; 7277 164th Avenue NE, Redmond, WA 98052 (US).
(72) **Inventors:** HEINONEN, Jari, M.; 2515 4th Avenue, Apt. 1808, Seattle, WA 98121 (US). HIRANO, Michael,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHODS AND APPARATUS FOR USE IN OBTAINING FRAME SYNCHRONIZATION IN AN OFDM COMMUNICATION SYSTEM



(S7) Abstract: Methods and apparatus suitable for use in obtaining frame synchronization in an Orthogonal Frequency Division Multiplexing (OFDM) communication system are described. The OFDM communication system includes a plurality of base units which simultaneously transmit a plurality of pilot tones in a predetermined pilot tone pattern during one or more time slots of a plurality of time slots defining a message slot. The method includes the steps of receiving OFDM signals within a time slot; determining a signal level in the OFDM signals at each frequency of a plurality of pilot tone frequencies; performing a correlation between the signal levels and the predetermined pilot tone pattern; generating and storing a pattern detection value based on performing the correlation; and repeating the receiving, determining, performing, generating and storing for each time slot of the plurality of time slots. The method includes the further steps of repeating, for a plurality of message frame durations, the above steps of repeated receiving, determining, performing, and generating to produce a plurality of averaged pattern detection values; performing a correlation between the plurality of averaged pattern detection values and a predetermined message frame pattern; and detecting a boundary of a message slot based on performing the correlation.

WO 01/97478 A2